

Vaisala Sounding Processing Subsystem SPS311G



Features

- Software Defined Radio technology for outstanding telemetry link performance and bandwidth efficiency
- Optimum performance when used with the Vaisala RS41 Radiosonde family.

The Vaisala Sounding Processing Subsystem SPS311G is the latest generation of the SPS-series for the Vaisala DigiCORA® Sounding System MW41. The SPS311G makes extensive use of Software Defined Radio (SDR) technology for receiving radiosonde signals. SDR technology is mature and commonly used today in a wide range of products including cellular base stations, military communication systems and public safety radios.

Radio Technology Programmed in Software

In the SPS311G, most of the radio technology is programmed in

software to work with a powerful Digital Signal Processor (DSP). This greatly improves flexibility and the future upgradability of both the hardware and software. The SPS311G's SDR receiver works with the Vaisala RS41 radiosonde family. When used with the Vaisala RS41 Radiosondes, the SPS311G offers excellent telemetry link performance and bandwidth efficiency.

As a sounding progresses, the SPS311G receives the radiosonde and GPS signals by means of the SDR receiver and local antennas. The SPS311G decodes the data and relays it to the sounding workstation for processing and archiving.

Technical Data

General

Dimensions	235 x 335 x 184 mm
Power consumption	70 W max.
Mains voltage	90 ... 132 V or 175 ... 264 V
Mains frequency	47 ... 63 Hz
DC power connection	18 ... 36 VDC, 60 W max.
Weight	7.5 kg max.
Cooling system	Forced air convection, three fans
Connectors	
UHF Coaxial	N-type female
GPS Coaxial	TNC-type female
VLF Coaxial	C-type female

Antenna amplifiers are powered through antenna cables

Radio Receiver System

Modulation	GFSK
Frequency range	400.15 ... 406 MHz
Sensitivity	-120 dBm: RS41-SG, RS41-SGP, RS41-SGM
Noise figure	<2.5 dB
Image rejection	70 dB
Spurious Free Dynamic Range	90 dB
Third Order Intercept Point (IIP3)	0 dBm
Input impedance	50 Ohms

(specifications valid with Vaisala telemetry antennas)

Environmental Conditions

Operating temperature range	0° C ... 45° C
Operating humidity	10 ... 90 %RH (non-condensing)
Storage temperature	-55° C ... 70° C
Storage humidity	5 ... 95 %RH

VAISALA

www.vaisala.com

Please contact us at
www.vaisala.com/requestinfo



Scan the code for
more information

Ref. B210492EN-E ©Vaisala 2016
This material is subject to copyright protection, with all copyrights retained by Vaisala and its individual partners. All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of Vaisala is strictly prohibited. All specifications — technical included — are subject to change without notice.

