

Vaisala Temperature Probe HMP110T

Vaisala Temperature Probe		HMP110T								PRICE
1	Output signals	0...1 V 0...2.5 V 0...5 V 1 ...5V Scaling for 4..20 mA converter (channel 1 only) RS485 Interface for Vaisala devices (VDIGI)	A B C D I R V							
2	Analog output range	RS485 or VDIGI -40 ... +60°C -40 ... +80°C		0 2 5						
3	Sensor protection	Plastic grid with filter <i>Plastic grid</i> <i>Stainless steel sintered filter</i>			A B C					
		Pair of plastic nuts						1		
		Probe holder for HMT120/130/140						2		
		Duct installation kit 215619						3		
5	Probe cable length	No cable 60 °C cable 0.3 m HMP50Z032 60 °C cable 3 m HMP50Z30A High temperature cable 1.5 m High temperature cable 3 m 180 °C FEP cable 3m 226902 180°C FEP cable 1.5m 238025						1 2 3 4 5 F J		
6	User guide	No user guide Multilingual quick guide							A B	
7	Loop power converter	No converter 4...20 mA loop power converter Always use single unit package								0 1 2
									TOTAL	
									QTY	
									TOTAL VALUE	

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMP110T	V	0	B	2	1	A	0
---------	---	---	---	---	---	---	---